

Company Profile

Simanto Vitrified LLP - India is committed to manufacture and supply product of consistently high and reliable quality to meet and / or exceed the customer's expectation and special needs with accepted international standards of Quality, Safety and Reliability.

Home furnishing requires striking a balance between style and functionality, and flooring are the expression of an ongoing desire to understand changing demands and living styles and to stay one step ahead of design and lifestyle trends. The key concepts here are creativity and customization, technology and beauty, comfort and style.

INDEX







GALAXY WHITE (L) 600x600mm





















GALAXY GOLD (L) 600x600mm







GALAXY MARBLE (L) 600x600mm





















GALAXY SANDY (L) 600x600mm







GALAXY PISTA (L) 600x600mm





















GALAXY CHOCOLATE (L) 600x600mm







DOUBLE CHARGE VITRIFIED TILES GALAXY SERIES

























GALAXY BLACK (D) 600x600mm






















GALAXY GRANITE (D) 600x600mm







GALAXY GREEN (D) 600x600mm























GALAXY TIGER (D) 600x600mm






























GALAXY ASH (D) 600x600mm







ALPS WHITE (L) 600x600mm






















ALPS SERIES



ALPS GOLD (L) 600x600mm







ALPS GREY (D) 600x600mm




















ALPS SERIES



ALPS VOLCANO (D) 600x600mm







ALPS BLACK (D) 600x600mm




















ALPS SERIES



ALPS BLUE (D) 600x600mm













600x600mm



















CRETA VENILA (L) 600x600mm






















CRETA ROSE (L) 600x600mm







CRETA FERRY (L) 600x600mm




















CRETA SERIES



CRETA BUTTER SCOTCH (D) 600x600mm







CRETA BLACK PEARL (D) 600x600mm




















CRETA SERIES



CRETA ZEBRA (D) 600x600mm







DRAGON SKY (L) 600x600mm





















DRAGONSERIES



DRAGON GOLD (L) 600x600mm







DRAGON CHIKU (L) 600x600mm




















DRAGONSERIES



DRAGON WHITE (L) 600x600mm





























DRAGON SERIES



DRAGON BLACK (D) 600x600mm







DRAGON SILVER (D) 600x600mm






























CRYSTAL LEMON (L) 600x600mm




















CRYSTAL SERIES



CRYSTAL ROSIT (L) 600x600mm







CRYSTAL WHITE (L) 600x600mm





















CRYSTAL SERIES



CRYSTAL ALMOND (D) 600x600mm







CRYSTAL BRONZE (D) 600x600mm




















CRYSTAL SERIES



CRYSTAL OCEAN (D) 600x600mm





TECHNICAL SPECIFICATION

SR. NO.	CHARACTERISTIC	STANDARD AS PER ISO-13006/EN14411 GROUP Bla	VALUES DECLARED BY SIMANTO	TEST METHOD
A.	REGULATORY PROPERTIES			
1.	DEVIATION IN LENGTH & WIDTH	± 0.5%	± 0.1%	ISO-10545-2
2.	DEVIATION IN THICKNESS	± 5.0%	± 2.0%	ISO-10545-2
3.	STRAIGTHNESS OF SIDES	± 0.5%	± 0.1%	ISO-10545-2
4.	RECTANGULARITY	± 0.5%	± 0.1%	ISO-10545-2
5.	SURFACE FLATNESS	± 0.5%	± 0.1%	ISO-10545-2
6.	COLOR DIFFERENCES	UNALTERED	NO CHANGE	ISO-10545-16
7.	GLOSSINESS	AS PER MANUFACTURER	MIN. 70%	GLOSSOMETER
B.	STRUCTURAL PROPERTIES			
1.	WATER ABSORPTION	≤ 0.5%	< 0.05%	ISO-10545-3
2.	APPARENT DENSITY	> 2.0 gm/cc	> 2.28 gm/cc	DIN 51082
C.	MASSIVE MECHANICAL PROPER	TIES		
1.	FLEXURAL MODULUS OF RUPTURE	MIN 35N/mm ²	MIN 40N/mm ²	ISO-10545-4
2.	FLEXURAL BREAKING STRENGTH	min 1300 n	MIN 2000 N	ISO-10545-4
3.	IMPACT RESISTANCE	AS PER MANUFACTURER	MIN 0.55	ISO-10545-5
D.	SURFACE MECHANICAL PROPER	RTIES		
1.	DEEP ABRASION RESISTANCE	MAX 175mm³	MAX 138mm ³	ISO-10545-6
2.	MOH'S HARDNESS	MIN 6	7	EN101
E.	THERMO HYGROMETRIC PROPE	RTIES		
1.	FROST RESISTANCE	NO DAMAGE	FROST PROOF	ISO-10545-12
2.	THERMAL SHOCK RESISTANCE	NO DAMAGE	NO DAMAGE	ISO-10545-9
3.	MOISTURE EXPANSION	NIL	NIL	ISO-10545-10
4.	THERMAL EXPANSION	MAX 9.0 x 10 ⁻ 6	MAX 6.5 x 10 ⁻ 6	ISO-10545-8
F.	CHEMICAL PROPERTIES			
1.	CHEMICAL RESISTANCE	NO DAMAGE	NO DAMAGE	ISO-10545-13
2.	STAIN RESISTANCE	RESISTANT	RESISTANT	ISO-10545-14
F.	SAFETY PROPERTIES			
1.	SLIP RESISTANCE(FRICTION CO EFFICENT)	> 0.40	> 0.40	ISO-10545-17

PACKING DETAILS


Size	No.of Tiles / Box	Coverage Area	Wt. of Box
600x600mm	4 Pcs.	1.44 Sq.Mtr.	26.50 Kg. (Approx)
600x1200mm	2 Pcs.	1.44 Sq.Mtr.	28.50 Kg. (Approx)


Note: Colour Shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the file before ordering. Every effort has been made to ensure the accuracy of the information given. However, the company reserve the right to change the specifications without prior notice. Sometime variations in shade of size being inherent to ceramic industry may occur. Before fixing, we advise you to follow the fixing instructions on the contants of the files as no responsibility can be accepted by company once the files have been fixed.



TILE INSTALLATION GUIDE

Simanto Vitrified Manufacturing Double Charge Vitrified Tiles using machinery of latest Italian Technology and best Quality Raw materials, So use proper and perfect Installations way to avoid bending, Shade variation and sizing problems.





- Place all the arrows in same direction
- Maintain perfect level at point (1) and (2) as shown in picture
- Bending up to 0.5mm is valid in ceramic industry as mentioned in catalogue. (Zero Bending is not possible)

Note: Please install tiles as illustrated. Company is not responsible after installation.





SIMANTO VITRIFIED LLP Jetpar Road, Opp. Viratnagar, At. Haripar-363 630. Tal. & Dist Morbi-363642 Gujarat INDIA.

www.simantovitrified.com

